


Original Date: 2015/12/30
Project Number: MRL

ECO Number: ECORL0042

Document: TDA476BH1
Page 1 of 111

MRL Field Installation Manual



Prepared By:	Checked By:	Approved By:	
Jie Xu	Haiyan Wang	Jian Yang	

Table of Contents


MRL Field Installation Manual	1
1 Safety rules	5
2 Storage and transport	6
2.1 Storage	6
2.2 Transport.....	6
3 Preparation before installation	7
3.1 Set up scaffold.....	8
3.2 Installation of landing door protection handrail.....	12
3.3 Set up sample framework.....	13
4 Installation of guide rail.....	15
4.1 Guide rail transport and storage.....	16
4.2 Installation of rail bracket	17
4.3 Installation of rail seat.....	20
4.4 Installation of guide rail	21
4.5 Correction of guide rail	24
4.6 Installation of oil catcher	27
5 Installation of landing door	28
5.1 Installation of landing door sill.....	29
5.2 Installation of landing door jamb.....	32
5.3 Installation of landing door header	35
5.4 Installation of landing door panel.....	39
5.5 Installation of door close weight.....	41
5.6 Adjust landing door lock	42
6 Installation of machine	43
6.1 Installation of rope hitch plate(on the beam).....	44
6.2 Installation of rope hitch plate(on the rail).....	45
6.3 Installation of machine beam	46
6.4 lifting of machine	48
6.5 Installation of machine	49
7 Installation of counterweight.....	51
7.1 Installation of counterweight frame	52
7.2 Installation of counterweight accessories	53
7.3 Installation of counterweight screen	56
8 Installation of car frame	58
8.1 Installation of sub-frame.....	59
8.2 Installation of bottom guide	60
8.3 Installation of uprights	61
8.4 Installation of crosshead.....	62
8.5 Installation of top guide	63
8.6 Installation of top of car sheave.....	64
8.7 Installation of platform	65
9 Installation of traction rope.....	66

10	Installation of hoistway mechanical components	69
10.1	Installation of pit ladder.....	70
10.2	Installation of speed governor	71
10.3	Installation of tension device	72
10.4	Installation of speed governor rope.....	74
10.5	Installation of buffer	75
11	Installation electrical components in hoistway	77
11.1	Installation of controller	77
11.2	Installation of machine wiring	78
12	Installation of cab.....	80
12.1	Installation of car panel	81
12.2	Installation of car ceiling.....	83
12.3	Installation of TOC handrail	85
12.4	Installation of car fan	86
12.5	Installation of TOC junction box.....	87
12.6	Installation of kick plate.....	88
12.7	Installation of car floor.....	89
12.8	Installation of load weighing device	90
13	Installation of car door system.....	91
13.1	Installation of door operator	92
13.2	Installation of car door panel.....	93
13.3	Installation of door vane	96
13.4	Installation of door protection device	97
14	Installation of position reference system	98
14.1	Installation of limit switch.....	99
14.2	Installation of leveling device	101
15	Installation of wiring.....	102
15.1	Installation of travelling cable.....	102
15.2	Installation of hoistway wiring.....	104
15.3	Installation of hoistway light.....	105
15.4	Installation of pit wiring.....	106
15.5	Installation of car wiring	107
15.6	Installation of inter-communication device.....	108
16	Installation of human interface device	109
16.1	Installation of car operation panel.....	109
16.2	Installation of hall buttons panel	110
17	Installation of compensation chain.....	111
	Annex	112

1 Safety rules

All field staff is under an obligation to keep below rules:

- 1) Keep work place cleanly;
- 2) There shall have sufficient light at work place;
- 3) The safety device shall be maintained regularly or replaced if necessary;
- 4) The lifting equipment must be examined before put in to use;
- 5) Carry a heavy load we must maintain the correct posture in order to avoid bodily injury;
- 6) Make sure the machine room door locked;
- 7) All field staff must wear personal protective products: helmet, goggles, safety gloves, overalls, safety belt, safety shoes;



2 Storage and transport

2.1 Storage

The packing boxes must be stacked at cleanly, dry place and with awning at jobsite. Pay attention there is no combustibles around packing boxes, oxygen cutting or any other incendive job was interdicted.

All the packing boxes shall be stacked on thick plank, make sure the water on floor can't damp the boxes.

The packing boxes shall not stack at heavy traffic area. All the packing boxes shall be covered by canvas and fastened by rope to avoid blow away. Security is necessary to insure all the material not be stole or damaged.

The packing boxes shall not be stacked too high. The heavier boxes shall be stacked below the light boxes. Anything stack on guide rail is interdicted.

The packing boxes shall be ordered stacked according the installation process. The packing boxes for same elevator shall be stacked separated and do not fixed with other elevator.

The elevator material stored at outside is not allowed anytime!

2.2 Transport

Please very carefully when transport elevator material at jobsite, make sure there is no damage on elevator material.

Use mechanical device to pull the elevator material is not allowed, especially guide rail. The appropriate device shall be used to transport cumbersome material.

Always comply with safety rules of lifting. The inexperience worker must be under guidance by specialize worker for the lifting work.

Only the lifting device with regular maintenance can be use for lifting.

3 Preparation before installation

The preparation of Project engineers and project supervisors:

Before installation, project engineers or project supervisors will carefully check and measure the installation field according to the construction drawing, which includes the check or the measuring of the landing numbers, the height of the top floor, the depth of the pit, the height of the elevators (or lifts) as well as the dimension and verticality of the rail well. They will also check whether the preformed hole of the hall doorway, the embedded part of the rail well as well as the preformed hole site in the machine room and the like are in consistency with the drawings or not. Afterwards, they will make an attentive analysis and research on the construction field so as to ensure a smooth installation of the elevators (or lifts).

Project engineers and project supervisors should have the knowledge about the power supply in actual use, the power supply for temporary use during the installation and the illumination so that they are able to work out a plan about the layout of the electrical equipment, the power supply for temporary use as well as the field illumination and afterwards timely come into contact with party A for help.


In light of the actual situation, project engineers should work out an installation plan and work assignments for all the departments engaged in the construction work.

The preparation of installation workers:

The installation personnel should be equipped with the basic knowledge about the type, specification as well as the properties of elevators (or lifts) and should also be familiar with installation diagrams, electrical diagrams and wire diagrams.

3.1 Set up scaffold

Scaffold overview:



Step	Instruction	Fig
1	Define the scaffold position in hoistway.	Figure 3-1 Figure 3-2
2	Install scaffold from bottom to top.	Figure 3-3
3	Detailed description of working platform.	Figure 3-4




Figure 3-1 (Rear Counterweight)




Figure 3-2 (Side Counterweight)




Figure 3-3




Figure 3-4

3.2 Installation of landing door protection handrail

Step	Instruction	Fig
1	Install landing door protective devices at each floor.	Figure 3-5




Figure 3-5

3.3 Set up sample framework

Step	Instruction	Fig
1	Find out the position of 6 plumb lines.	Figure 3-6
2	Build upper sample plate and lower sample plate.	Figure 3-7




Figure 3-6





Figure 3-7

Notes: here gives one type of sample frameworks. Other appropriate method of sample frameworks can be used.

4 Installation of guide rail

Guide rail installation overview:



4.1 Guide rail transport and storage

4.1.1 Transport




Figure 4-1

4.1.2 Storage




Figure 4-2

4.2 Installation of rail bracket

4.2.1 Installation car rail bracket

Step	Instruction	Fig
1	The position of rail bracket in hoistway.	Figure 4-3
2	Connect the fixed support on the well wall.	Figure 4-4
3	Connect the rail support on fixed support.	Figure 4-5




Figure 4-3




Figure 4-4




Figure 4-5

4.2.2 Installation counterweight rail bracket

Step	Instruction	Fig
1	Connect the fixed support on the well wall.	Figure 4-6
2	Connect the rail support on fixed support.	Figure 4-7




Figure 4-6




Figure 4-7

4.3 Installation of rail seat

Step	Instruction	Fig
1	Connect the rail seat on the pit floor.	Figure 4-8






Figure 4-8

4.4 Installation of guide rail

4.4.1 Installation of car guide rail

Step	Instruction	Fig
1	Connect the rails on the rail brackets by clips.	Figure 4-9
2	Connect the top rails on the rail brackets by clips.	Figure 4-9a
3	Connected the rail to the rail by fishplate.	Figure 4-10

In order to guarantee the quality of the connection point, the machining end faces and fishplates must be thoroughly clean.






Figure 4-10

4.4.2 Installation of counterweight guide rail

Step	Instruction	Fig
1	Connect the rails on the rail brackets by clips.	Figure 4-11
2	Connected the rail to the rail by fishplate.	Figure 4-12




Figure 4-11




Figure 4-12

4.5 Correction of guide rail

Step	Instruction	Fig
1	Measure distance between the plumb line and the top surface of guide rails with a steel ruler and estimate whether the distance is of too much deviation from 30mm or not. If this is the case, add or remove some shims, or adjust rail brackets when necessary.	Figure 4-13
2	Measure plumb between the plumb line and the surface of guide rails with guide rail calipers. Calibrate guide rails with a hammer when the deviation is too large.	Figure 4-14
3	The deviation for guide relative to standard baseline.	Figure 4-15
4	Calibrate distortion of guide rail sides with a guiding rule.	Figure 4-16
5	Trimming of guide rails at the location of rail joints.	Figure 4-17
6	The deviation of the distance between the top faces of two guide rails.	Figure 4-18




Figure 4-13




Figure 4-14




Figure 4-15




Figure 4-16




Figure 4-17




Figure 4-18

4.6 Installation of oil catcher

Step	Instruction	Fig
1	Fix the slot of the oil catcher to the guide rail of the elevator, and the width of the slot shall be fit with that of the guide rail.	Figure 4-19





Figure 4-19

5 Installation of landing door

Landing door installation overall picture:



5.1 Installation of landing door sill

Step	Instruction	Fig
1	Mark door open center line and open width lines on the sill.	Figure 5-1
2	Assemble brackets and landing door sills	Figure 5-2
3	Position the landing door sill assembly in hoistway and make open width line on sill aligned with plumb line.	Figure 5-3
4	Fix sill assembly via hilti bolts on the wall, and adjust the sill so that aligning the clean opening door width lines with two plumbs for landing door.	Figure 5-4, 5-5, 5-6
5	Connect guard plate to the sill with fasteners	Figure 5-7




Figure 5-1




Figure 5-2




Figure 5-3




Figure 5-4




Figure 5-5




Figure 5-6




Figure 5-7

5.2 Installation of landing door jamb

Step	Instruction	Fig
1	Assembly landing door jamb at landing.	Figure 5-8
2	Connect the jamb to the sill.	Figure 5-9
3	Connect the jamb on the well wall.	Figure 5-10




Figure 5-8




Figure 5-9




Figure 5-10

5.3 Installation of landing door header

Step	Instruction	Fig
1	Assemble the brackets to the landing door header.	Figure 5-11
1	Connect the landing door header to the door jamb.	Figure 5-12
2	Connect the landing door header on the well wall.	Figure 5-13
3	Adjust the landing door header.	Figure 5-14, 5-15




Figure 5-11




Figure 5-12




Figure 5-13




Figure 5-14




Figure 5-15

5.4 Installation of landing door panel

Step	Instruction	Fig
1	Connect landing door panel to door header and assemble guide shoes.	Figure 5-16
2	Install another panel by same way.	N/A
3	Adjust the door panel.	Figure 5-17





Figure 5-16



Adjust four up thrust rollers on hanging plate to keep 0.2~0.5mm clearance between roller and rail.





Figure 5-17

5.5 Installation of door close weight

Step	Instruction	Fig
1	Connect the door close weight to the door header.	Figure 5-18
2	Connect the cover plate to the door header.	Figure 5-19





Figure 5-18



Cross pan head screws.
 M8X20

Figure 5-19

5.6 Adjust landing door lock

Step	Instruction	Fig
1	Adjust landing door lock clearance.	Figure 5-20





Figure 5-20

Notice:


1. The mesh depth of lock hook and lock tongue should be not less than 7mm.
2. To keep 2mm clearance between lock hook and lock tongue.
3. Lock hook and lock tongue should be full mesh in level direction.
4. Active contact and still contact of door lock should be centered mesh; the compression of the contact should

6 Installation of machine

Machine installation overall picture:



rope hitch plate on the beam



rope hitch plate on the rail

6.1 Installation of rope hitch plate(on the beam)

Step	Instruction	Fig
1	Put the rope hitch beam on the bearing plate and adjust it refer to the layout. After adjustment, fix them onto the bearing plate by welding.($>630\text{kg}$)	Figure 6-1




Figure 6-1

6.2 Installation of rope hitch plate(on the rail)

Step	Instruction	Fig
1	Put the rope hitch beam on the rail.	Figure 6-2




Figure 6-2

6.3 Installation of machine beam

Step	Instruction	Fig
1	Put the connection plate on the bearing plate and adjust it refer to the layout. After adjustment, fix them onto the bearing plate by welding.	Figure 6-3
2	Put the cover in the hole.	Figure 6-3




Figure 6-3

Step	Instruction	Fig
3	Connect rubbers to connection plates.	Figure 6-4
4	Connect machine beams to rubbers.	Figure 6-5




Figure 6-4




Figure 6-5

6.4 lifting of machine

Step	Instruction	Fig
1	Connect the chain block to the lifting hooks.	Figure 6-6
2	Use the chain block lift the machine.	Figure 6-7




Figure 6-6




Figure 6-7

6.5 Installation of machine

Step	Instruction	Fig
1	Connect the machine to the beam.	Figure 6-8
2	Adjust the traction sheave.	Figure 6-9
3	Installation bolt to protect the beam	Figure 6-10




Figure 6-8




Figure 6-9





Figure 6-10

7 Installation of counterweight

Counterweight installation overview:



7.1 Installation of counterweight frame

Step	Instruction	Fig
1	Connect the counterweight base under the frame.	Figure 7-1
2	Place the CWT frame on the upper part.	Figure 7-2






Figure 7-1



$H = \text{Buffer base height} +$
 $\text{Buffer height} + \text{CWT}$
 runby

Figure 7-2

7.2 Installation of counterweight accessories

Step	Instruction	Fig
1	Install the guide shoes on the side of counterweight frame.	Figure 7-3
2	Add counterweight filler into the counterweight frame.	Figure 7-4
3	Install the counterweight filler pressing plates.	Figure 7-5
4	Install the oil bottle on the counterweight.	Figure 7-6




Figure 7-3




Figure 7-4




Figure 7-5




Figure 7-6

7.3 Installation of counterweight screen

Step	Instruction	Fig
1	The distance from the bottom of the screen to the pit floor is less than 300mm.	Figure 7-7
2	Connect the support on the frame of counterweight screen.	Figure 7-8
3	Connect the counterweight screen net on the guide rail.	Figure 7-9




Figure 7-7




Figure 7-8





Figure 7-9

8 Installation of car frame

Car Frame installation overview:



8.1 Installation of sub-frame

Step	Instruction	Fig
1	Remove the scaffold in the top of hoist-way.	Figure 8-1
2	Put sub-frame in to hoistway and adjust the horizontality.	Figure 8-1




Figure 8-1

8.2 Installation of bottom guide

Step	Instruction	Fig
1	Install the bottom guide shoes on safety gear.	Figure 8-2




Figure 8-2

8.3 Installation of uprights

Step	Instruction	Fig
1	Fix bottom of uprights on the sub-frame.	Figure 8-3




Figure 8-3

8.4 Installation of crosshead

Step	Instruction	Fig
1	Installation of cross-head beam.	Figure 8-4




Figure 8-4

8.5 Installation of top guide

Step	Instruction	Fig
1	Installation of top guide shoes, fix on the crosshead.	Figure 8-5




Figure 8-5

8.6 Installation of top of car sheave

Step	Instruction	Fig
1	Install top of car sheave on crosshead.	Figure 8-6
2	Connect the sheave guard on crosshead.	Figure 8-7




Figure 8-6




Figure 8-7

8.7 Installation of platform

Step	Instruction	Fig
1	Install car door sill support and sill.	Figure 8-9
2	Install the toe guard to the bracket of sill.	Figure 8-10




Figure 8-9




Figure 8-10

9 Installation of traction rope

Step	Instruction	Fig
1	Hanging method of steel wire rope.	Figure 9-1
2	Hanging method of steel wire rope (top view).	Figure 9-2
3	Connect the end of rope with rope termination; Fox termination on dead-end hitch plate.	Figure 9-3
4	Install termination anti-rotate rope.	Figure 9-4








Figure 9-1



Detail I



Detail II



Detail III

Figure 9-2




Figure 9-3





Figure 9-4

10 Installation of hoistway mechanical components

Hoistway mechanical components installation overview:



10.1 Installation of pit ladder

Step	Instruction	Fig
1	Stand the bottom of the pit ladder on the pit floor.	Figure 10-1
2	Connect the pit ladder on the well wall.	Figure 10-2




Figure 10-1






Figure 10-2

10.2 Installation of speed governor

Step	Instruction	Fig
1	Connect the speed governor on the beam.	Figure 10-3a/b



10.3 Installation of tension device

Step	Instruction	Fig
1	The distance from the bottom of the tension device to the pit floor is 150~250mm.	Figure10-4
2	Connect the plate of tension device on the car rail.	Figure 10-5
3	Connect the weight part of tension device on the plate of tension device.	Figure 10-6
4	Connect the switch on the tension device.	Figure 10-7




Figure 10-4




Figure 10-5




Figure 10-6




Figure 10-7

10.4 Installation of speed governor rope

Step	Instruction	Fig
1	Install the governor rope on governor and tension device, fix the both ends of governor rope to the safety linkage on the car frame by rope clips.	Figure 10-8




Figure 10-8

10.5 Installation of buffer

Step	Instruction	Fig
1	Fix the buffer base on the pit floor.	Figure 10-9
2	Connect the oil buffer on the buffer base.	Figure 10-10
3	Connect the PU buffer base on the pit floor.	Figure 10-11




Figure 10-9




Figure 10-10




Figure 10-11

11 Installation electrical components in hoistway

11.1 Installation of controller

Step	Instruction	Fig
1	Connect the controller on the wall.	Figure 11-1




Figure 11-1

11.2 Installation of machine wiring

Step	Instruction	Fig
1	Fix the cable tube on the wall.	Figure 11-2





Figure 11-2

12 Installation of cab

Cab installation overall picture:



12.1 Installation of car panel

Step	Instruction	Fig
1	Install the panels on the platform according sequence.	Figure 12-1
2	Install the first and second panels on the platform.	Figure 12-2
3	Install other side and rear panels on the platform with the same way.	Figure 12-3




Figure 12-1




Figure 12-2




Figure 12-3

12.2 Installation of car ceiling

Step	Instruction	Fig
1	Install the car ceiling on the wall panels.	Figure 12-4
2	Install the front panels.	Figure 12-5
3	Install the cab steadiers on the ceiling.	Figure 12-6




Figure 12-4




Figure 12-5




Figure 12-6

12.3 Installation of TOC handrail

Step	Instruction	Fig
1	Connect the both side TOC handrail to the crosshead.	Figure 13-7
2	Connect the back side handrail to the side handrail.	Figure 13-8




Figure 13-7




Figure 13-8

12.4 Installation of car fan

Step	Instruction	Fig
1	Connect the car fan to the ceiling.	Figure 12-10




Figure 12-10

12.5 Installation of TOC junction box

Step	Instruction	Fig
1	Connect the junction box to the handrail.	Figure 12-11




Figure 12-11

12.6 Installation of kick plate

Step	Instruction	Fig
1	Connect the kick plate on the car ceiling.	Figure 12-12




Figure 12-12

12.7 Installation of car floor

Step	Instruction	Fig
1	Glue the PVC floor on the platform.	Figure 12-13, 12-14




Figure 12-13




Figure 12-14

12.8 Installation of load weighing device

Step	Instruction	Fig
1	Connect the bolt assembly at bottom of platform.	Figure 12-15
2	Fix the load sensor on sub-frame.	Figure 12-15





Figure 12-15

13 Installation of car door system

Car door system installation overview:



13.1 Installation of door operator

Step	Instruction	Fig
1	Connect the brackets on car ceiling.	Figure 13-1
2	Connect the door operator on brackets.	Figure 13-2




Figure 13-1




Figure 13-2

13.2 Installation of car door panel

Step	Instruction	Fig
1	Connect car door panel to door operator and assemble guide shoes.	Figure 13-3
2	Install another panel by same way.	N/A
3	Adjust the door panel.	Figure 13-4, 13-5




Figure 13-3




Figure 13-4




Figure 13-5

13.3 Installation of door vane

Step	Instruction	Fig
1	Connect door vane on door operator.	Figure 13-6
2	Adjust of door vane.	Figure 13-7




Figure 13-6




Figure 13-7

13.4 Installation of door protection device

Step	Instruction	Fig
1	Installation of light curtain.	Figure 13-8





Figure 13-8

14 Installation of position reference system

Position reference system installation overview:



14.1 Installation of limit switch

Step	Instruction	Fig
1	Connect the limit switch support on the guide	Figure 14-1
2	Connect the cam on the upright.	Figure 14-1
3	The switches installation dimension in the different elevator rated speed.	Figure 14-2




Figure 14-1




Figure 14-2

The switches installation dimension in the different elevator rated speed, shown as below. (unit: mm)

(The switches installation dimension should be the distance between the car sill and the landing door sill at this floor when the car running to the top or bottom floor in inspection speed as well as the switch switches-off.)

Speed (m/s)	DLS2,ULS2	DLS1,ULS1	FLSD, FLSU
1.0/1.50/1.75		-2400 mm	+150mm
2.00/2.50	-4500 mm	-2400 mm	+150mm

14.2 Installation of leveling device

Step	Instruction	Fig
1	Connect the leveling sensor on the car cross-head.	Figure 14-3
2	Connect the leveling sensor trigger plate on the guide at each floor.	Figure 14-3




Figure 14-3

15 Installation of wiring

15.1 Installation of travelling cable

Step	Instruction	Fig
1	Fix the cable bracket on rail and sub-frame.	Figure 15-1/15-2
2	Fix the travelling cable on brackets.	Figure 15-1/15-2




Figure 15-1




Figure 15-2

15.2 Installation of hoistway wiring

Step	Instruction	Fig
1	Fix the hoistway wire on the wall.	Figure 15-3

1. Hall fixtures, door locks and other branches of cable should be fixed at both ends and corner.

2. The distance between hoist-way wires and car parts should be more than 20mm.

3. The ground wire of door lock must be connected to the main ground wire in hoist-way.

4. The hoist-way wire should be fixed well, cables should be roughly perpendicular. All the grounding system must be in connection.




Figure 15-3

15.3 Installation of hoistway light

Step	Instruction	Fig
1	Fix the lamp on wall and connect wiring.	Figure 15-4




Figure 15-4

15.4 Installation of pit wiring

Step	Instruction	Fig
1	The drawing for pit wiring.	Figure 15-5




Figure 15-5

15.5 Installation of car wiring

Step	Instruction	Fig
1	Connect car device wiring to junction box. Fix the wiring on the car by nylon ribbon.	Figure 15-6




Figure 15-6

15.6 Installation of inter-communication device

Step	Instruction	Fig
1	The drawing for inter-communication device.	Figure 15-7
2	Connect interphone car bottom unit on toe guard.	Figure 15-8




Figure 15-7

16 Installation of human interface device

16.1 Installation of car operation panel

Step	Instruction	Fig
1	Connect the car operation panel on the car panel.	Figure 16-1




Figure 16-1

16.2 Installation of hall buttons panel

Step	Instruction	Fig
1	Connect the hall buttons panel on the well wall by cement.	Figure 16-2




Figure 16-2

17 Installation of compensation chain

Step	Instruction	Fig
1	Connect the compensation chain under car sub-frame and counterweight frame.	Figure 17-1




Figure 17-1

Annex

Tightening torques of bolts

Thread M	Tensile stress area A_s [mm ²]	8.8 Zn chromated
		Tighten torque [Nm]
3	4.96	1.07
4	8.65	2.52
5	13.99	5.01
6	19.84	8.55
8	36.10	20.6
10	57.30	40.8
12	83.20	70.7
16	155	173
20	242	338
24	349	583
30	555	1150
36	809	2000
